

KWC F5E

Electronic pillar tap with battery operation

Modell-Linie: F5E | F5EV1001 Taps | Electronic taps



KWC-No.

2030027922

F5E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve cartridge, 6 V lithium battery (CR-P2) and sensor in all-metal housing, high-polished chromium-plated brass. Anti-theft aerator, design SLIM, with

volume flow rate at 3 bar

0.08 l/s

integrated flow regulator 5.0 l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Technical Data

| lechnical Data | | |
|--------------------------------|-----------------------------|--|
| with backflow preventer | no | |
| calculation flow rate cold wat | 0.1 l/s | |
| compatible A3000 open | no | |
| default automatic hygiene flus | 24h after the last activity | |
| depressurised | no | |
| with filter | yes | |
| functional principle | electronic self-closing | |
| hygiene flushing | yes | |
| diameter nominal | DN 15 | |
| inlet size | G 3/8 | |
| Locking mechanism | Top section, non-ceramic | |
| material fitting | brass | |
| minimum flow pressure | 1 bar | |
| type of mixing | no | |
| number of batteries | 1 | |
| Parameterization | remote control | |
| Pop-up waste set | no | |
| power supply connection | Battery 6 V | |
| power consumption | 1.5 Voltampere | |
| Type of power supply | Battery | |
| protective system IP | IP59K | |
| with rosettes/cover plate | no | |
| protective shutdown | yes | |
| sound insulation | no | |
| Spout | fixed | |
| | | |



KWC F5E

Electronic pillar tap with battery operation

Modell-Linie: F5E | F5EV1001 Taps | Electronic taps

| spout projection | | 125 mm | | | |
|--|-------------------------------|---|---------------------------------------|--------------------|--|
| surface finish fitting | | chromed | | - | |
| surface treatment fitting temperature limit thermal disinfection with transformer/power supply type of batteries type of mounting type of operation type of sensor type of tap volume flow rate at 3 bar | | polished no no no CR-P2 Lithium battery 6V tap hole | | = | |
| | | | | = | |
| | | | | - | |
| | | | | - | |
| | | | | - | |
| | | | | - | |
| | | sensor operation | | - | |
| | | opto-electronic sensor pillar tap 0.08 l/s | | = | |
| | | | | = | |
| | | | | - | |
| water connection | | hose (gland nut) | | = | |
| Accent colour | | none | | - | |
| Basic colour | | chrome-look (glossy) | | - | |
| | | - | | - | |
| Optional Accessories | | | | | |
| <u> </u> | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Bidirectional remote control for electronical fittings F3 and F5 and F5 | | control for fittings F3 | 3 5.0 I/min aerator, angle-adjustable | 3.0 I/min. aerator | |
| | | | 2030041326 | 2030041424 | |
| 2030036654 ACEX9005 | 2030036849 ACEX9004 | | ACXX1002 | ASXX1008 | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| MF AI | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Socket | | der-table thermostat | | | |
| | | der-table thermostat | | | |



KWC F5E

Electronic pillar tap with battery operation

Modell-Linie: F5E | F5EV1001 Taps | Electronic taps

Spare Parts





Solenoid valve cartridge

Mounting key

2030045522 ACXX9002

2030041329 ACXX1003