





KWC F5E-Mix
Electronic pillar mixer with in-wall power supply

Modell-Linie: F5 | F5EM1003
Taps | Electronic taps



KWC-No.
2030035329
2030039432
with flow regulator 3.0 l/min

volume flow rate at 3 bar
0.08 l/s
0.05 l/s

F5E-Mix pillar mixer DN 15 for sanitary facilities, opto-electronically controlled. For connection to hot and cold water via hoses with integrated backflow preventer and strainers. Control electronics, solenoid valve cartridge and sensor in all-metal housing, high-polished chromium-plated brass. Temperature lever with adjustable, turn-proof temperature stop as well as conversion set

for concealed mixing device. Anti-theft aerator, design SLIM, with integrated flow regulator 5.0 l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control. With in-wall power supply 100 - 240 V AC.

Technical Data

with backflow preventer
calculation flow rate cold wat
calculation flow rate hot water
compatible A3000 open
default automatic hygiene flush
depressurised
with filter
functional principle
hygiene flushing
diameter nominal
inlet size
Locking mechanism
material fitting
minimum flow pressure
type of mixing
Parameterization
Pop-up waste set
power supply connection
position of power connection
power consumption
Type of power supply
protective system IP
with rosettes/cover plate

yes
0.07 l/s
0.07 l/s
no
24h after the last activity
no
yes
electronic self-closing
yes
DN 15
G 3/8
Top section, non-ceramic
brass
1 bar
yes
remote control
no
100 - 240 V AC
from bottom
1.5 Voltampere
Transformer
IP59K
no




KWC F5E-Mix
Electronic pillar mixer with in-wall power supply

Modell-Linie: F5 | F5EM1003
Taps | Electronic taps

protective shutdown	yes
sound insulation	no
Spout	fixed
spout projection	125 mm
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	no
with transformer/power supply	yes
type of mounting	tap hole
type of operation	sensor operation
type of sensor	opto-electronic sensor
type of tap	pillar tap
volume flow rate at 3 bar	0.08 l/s
water connection	hose (gland nut)
Accent colour	none
Basic colour	chrome-look (glossy)

Optional Accessories




**Bidirectional remote control for
electronical fittings F3 and F5**

2030036654
ACEX9005




**2-button remote control for fittings F3
and F5**

2030036849
ACEX9004



Socket

2030040334
ACEX1001



Anti-twist protection for F5S

2030035383
ACXX1001



Extension cable 5 m

2030043814
ACEX9010




PURETHERM under-table thermostat

2030012758
PURE0031



5.0 l/min aerator, angle-adjustable

2030041326
ACXX1002




3.0 l/min. aerator

2030041424
ASXX1008



KWC F5E-Mix
Electronic pillar mixer with in-wall power supply

Modell-Linie: F5 | F5EM1003
Taps | Electronic taps



Aerator 1.8 l/min


2030041442
ACXX1005

Spare Parts



Aerator 5.0 l/min

2030041011
ASXX1004




Cap

2030041558
ASEX1007




Plug red

2030041951
ASEX1009




Plug blue

2030041952
ASEX1010




Solenoid valve cartridge

2030045522
ACXX9002




Temperature selection lever

2030041431
ASEM1001



Hose

2030041320
ASXM1001




Quick-action fastener

2030043596
ASEX1013



KWC F5E-Mix
Electronic pillar mixer with in-wall power supply

Modell-Linie: F5 | F5EM1003
Taps | Electronic taps




Water way

2030041949
ASEX1008




Sensor, ID 01/00004

2030041458
ASEX1005



In-wall power supply

2030039825
ACEX9003



Mounting key

2030041329
ACXX1003