


KWC

F3E Electronic bib tap with battery operation

Modell-Linie: F3 | F3EV1004 Taps | Electronic taps

-	



KWC-No.

2030036177

2030040224

with flow regulator 3.0 l/min

F3E bib tap DN 15 for wall mounting for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water. Control electronics, solenoid valve cartridge, 6 V lithium battery (CR-P2) and sensor in all-metal housing, high-polished ch romium-plated brass. Aerator with integrated flow regulator 6.0

volume flow rate at 3 bar

0.05 l/s

l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Technical Data

Technical Data	
with backflow preventer	no
calculation flow rate cold wat	0.1 l/s
compatible A3000 open	no
default automatic hygiene flus	24h after the last activity
depressurised	no
with filter	yes
functional principle	electronic self-closing
hygiene flushing	yes
diameter nominal	DN 15
Locking mechanism	Top section, non-ceramic
material fitting	brass
minimum flow pressure	1 bar
type of mixing	no
number of batteries	1
Parameterization	remote control
Pop-up waste set	no
power supply connection	Battery 6 V
power consumption	1.5 Voltampere
Type of power supply	Battery
protective system IP	IP59K
with rosettes/cover plate	no
protective shutdown	yes
sound insulation	no
Spout	fixed



KWC

F3E Electronic bib tap with battery operation

Modell-Linie: F3 | F3EV1004 Taps | Electronic taps

spout projection surface finish fitting surface treatment fitting temperature limit thermal disinfection		130 mm				
		chromed	polished			
		polished				
		no	no			
		automatic therma	automatic thermal disinfection			
with transformer/power supply		no	no			
type of batteries		CR-P2 Lithium ba	CR-P2 Lithium battery 6V			
type of mounting		wall mounting	wall mounting			
type of operation		sensor operation	sensor operation			
type of sensor		opto-electronic se	opto-electronic sensor			
type of tap		bib tap	bib tap			
volume flow rate at 3 bar		0.1 l/s	0.1 l/s			
water connection Accent colour		threaded connect	threaded connection (external) none			
		none				
Basic colour		chrome-look (glos	chrome-look (glossy)			
Optional Accessories						

Bidirectional remote control for electronical fittings F3 and F5

2-button remote control for fittings F3 and F5

Aerator

3.0 I/min. aerator

2030036654 ACEX9005

2030036849 ACEX9004

2000101160 ZAQUA087 **2030041424** ASXX1008

Extension adapter for F3E bib tap

2030043823 ACEV1001



KWC

F3E Electronic bib tap with battery operation

Modell-Linie: F3 | F3EV1004 Taps | Electronic taps

Spare Parts



Solenoid valve cartridge

2030045522 ACXX9002