



KWC F5LME  
Hybrid kitchen fitting

Modell-Linie: F5 | F5LME001  
Taps | Manual taps



KWC-No.

2030061048

F5LME hybrid kitchen fitting DN 15 as pillar mixer with swivelling spout, can be locked in the centre position. Adjustable swivel ranges of 50°, 120° and 360°. For connection to hot water and cold water via hoses with strainers. Single lever mixer with mixer cartridge with ceramic disc technology and adjustable, turn-proof temperature stop. Alternative activation using hand reflection via an opto-electronic sensor for time-controlled water release with preset mixing water temperature. Mixer cartridge, solenoid valve and sensor with control electronics in all-metal housing, brushed stainless steel. Laminar jet controller with integrated flow rate controller (8.0 l/min). Projection 220 mm. Activated water hygiene

flushing 24 hours after last activation, safety switch-off for continuous reflection and saving of statistical data. With option for parametrisation and communication via optional, bidirectional remote control. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting for installation under the kitchen sink or for separate power supply via 6.75 V/12 V DC power supply unit or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

depressurised	no
with filter	yes
functional principle	manual
hygiene flushing	prepared
diameter nominal	DN 15
Locking mechanism	Top section, non-ceramic
material fitting	stainless steel
minimum flow pressure	1 bar
type of mixing	yes
Pop-up waste set	no
with rosettes/cover plate	no
Spout	rotating, top
surface finish fitting	brushed
temperature limit	yes
thermal disinfection	yes
type of mounting	tap hole
type of operation	manual operation
type of tap	pillar tap
water connection	hose (gland nut)
Accent colour	none



Mandatory Accessories



**KWC F5LME**  
Hybrid kitchen fitting

**Modell-Linie: F5 | F5LME001**  
Taps | Manual taps




**Power supply unit**

**2030039477**  
ACEX9001



**Extension cable 5 m**


**2030043814**  
ACEX9010



**In-wall power supply**


**2030039825**  
ACEX9003

**Optional Accessories**



**Bidirectional remote control for  
electronical fittings F3 and F5**


**2030036654**  
ACEX9005



**2-button remote control for fittings F3  
and F5**

**2030036849**  
ACEX9004

**Spare Parts**



**Solenoid valve cartridge**

**2030045522**  
ACXX9002



**Backflow preventer DN 6**

**2030045816**  
ASXX9002