

Modell-Linie: F4 | F4ET1001
Umyvadlové armatury | Elektronické armatury



KWC-No.
2030072424

F4ET-Med thermostatic wall-mounted mixer as DN 15 wall-mounted mixer, for wall mounting with lockable swivelling spout, for sanitary facilities in the healthcare and nursing sector. Opto-electronically controlled, triggered by hand movement with subsequent automatic switching to body detection. Thermostat with metal handle, including lever for reduced-touch operation, and adjustable, turn-proof temperature stop. With the option of manual thermal disinfection. For connecting to hot and cold water. Control electronics, stagnation-free hygiene solenoid valve cartridge, flow rate controller 9.0 l/min, 6 V lithium battery (CR-P2) and sensor in the scald-protected safe-touch housing, polished chromium-plated

brass. Decoupled from the tap housing, volume-reduced, smooth water flow from low-lead brass (lead proportion ≤ 0.2%), and without nickel coating. With thermal insulation components to reduce heat transfer from the tap housing to the cold-water line. Self-emptying spout with laminar jet controller. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes. 210 mm projection. Activated water hygiene flushing 24 hours after last activation, safety switch-off for continuous reflection and saving of statistical data. With option for parametrisation and communication via optional, bidirectional remote control.

Technické údaje

ATT-WS-BACKFLOWPREVENTER
ATT-WS-COMPA3000O
Nastavené automatické hygienické proplachování
Snížený tlak
ATT-WS-FILTER
Nastavitelná doba průtoku
Ovládní
ATT-WS-HYGIENE-FLUSH
Nominální průměr
Velikost přívodní trubky
ATT-WS-LOCKINGMECHANISM
Materiál armatury
Maximální doba průtoku
Minimální tlak průtoku
Minimální doba průtoku
Typ směšování
Počet baterií
ATT-WS-PARAMETERIZATION
ATT-WS-POPUWASTESET
Napájení
ATT-WS-POWTYPE
ATT-WS-ROSETTES

ano
Ne
24 hodin po posledním použití
Ne
ano
ano
electronically self-closing
ano
DN 15
G 1/2 B
TOP-NONCERAMIC
mosaz
255
1
1
s termostatem
1
REMOTECONTROL
Ne
Baterie 6 V
BATTERY
ano

Modell-Linie: F4 | F4ET1001
Umyvadlové armatury | Elektronické armatury

Bezpečnostní vypnutí	ano
ATT-WS-SPOUT	ROTATING-BOT
Povrchová úprava armatury	chromovaný
ATT-WS-SURTREATFIT	POLISHED
Zakázkový	Ne
ATT-WS-TEMPERATURELIMIT	ano
Termická dezinfekce	MANUAL
ATT-WS-TRANSFORMER	Ne
Typ baterií	CR-P2
Způsob montáže	montáž na stěnu
Ovládání	senzor
Typ senzoru	optoelektronický senzor
Typ baterie	poplácí klepá
ATT-WS-WATCON	SUNION

Volitelné příslušenství



Obousměrné dálkové ovládání pro armatury F3 a F5

2030036654
ACEX9005



Dvoutlačítkové dálkové ovládání pro armatury f3 a f5

2030036849
ACEX9004
