




KWC

Modell-Linie: F4 | F4ET1001
Kranar | Elektronické armatury



KWC-No.

2030072424

F4ET-Med thermostatic wall-mounted mixer as DN 15 wall-mounted mixer, for wall mounting with lockable swivelling spout, for sanitary facilities in the healthcare and nursing sector. Opto-electronically controlled, triggered by hand movement with subsequent automatic switching to body detection. Thermostat with metal handle, including lever for reduced-touch operation, and adjustable, turn-proof temperature stop. With the option of manual thermal disinfection. For connecting to hot and cold water. Control electronics, stagnation-free hygiene solenoid valve cartridge, flow rate controller 9.0 l/min, 6 V lithium battery (CR-P2) and sensor in the scald-protected safe-touch housing, polished chromium-plated

brass. Decoupled from the tap housing, volume-reduced, smooth water flow from low-lead brass (lead proportion ≤ 0.2%), and without nickel coating. With thermal insulation components to reduce heat transfer from the tap housing to the cold-water line. Self-emptying spout with laminar jet controller. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes. 210 mm projection. Activated water hygiene flushing 24 hours after last activation, safety switch-off for continuous reflection and saving of statistical data. With option for parametrisation and communication via optional, bidirectional remote control.

Technical Data

ATT-WS-BACKFLOWPREVENTER
ATT-WS-COMPA3000O
Standard automatisk hygien spolning
Nedtryckt
ATT-WS-FILTER
Justerbar flödestid
Funktionell princip
ATT-WS-HYGIENE-FLUSH
Nominell diameter
Inbygggnadsmått
ATT-WS-LOCKINGMECHANISM
Material delar
Maximal flödestid
Minimalt flödestryck
Minimal flödes tid
Typ av blandning
Antal batterier
ATT-WS-PARAMETERIZATION
ATT-WS-POPUWASTESET
Kraft försörjnings anslutning
ATT-WS-POWTYPE
ATT-WS-ROSETTES

Ja
Nej
24H-AFTER-ACTIMTY
Nej
Ja
Ja
Elektronisk självstängande
Ja
DN 15
G 1/2 B
TOP-NONCERAMIC
Mässing
255
1
1
Med termostat
1
REMOTECONTROL
Nej
Batteri 6 V
BATTERY
Ja



KWC

Modell-Linie: F4 | F4ET1001
Kranar | Elektronické armatury


Säkerhetsavstängning	Ja
ATT-WS-SPOUT	ROTATING-BOT
yt finish	Förkromad
ATT-WS-SURTREATFIT	POLISHED
ATT-WS-TAILMADE	Nej
ATT-WS-TEMPERATURELIMIT	Ja
terminal för desinfektion	MANUAL
ATT-WS-TRANSFORMER	Nej
Typ av batterier	CR-P2
Typ av montering	Väggmontering
Typ av operation	Sensor styrning
Typ av sensor	Utan elektronisk sensor
Typ av kran	Tvågreppsblandare
ATT-WS-WATCON	SUNION

Extratillbehör



Bidirectional remote control for
electronical fittings F3 and F5

2030036654
ACEX9005



2-button remote control for fittings F3
and F5

2030036849
ACEX9004