



KWC-No.

3600000189

F4MT-Med thermostat bath mixer with fixed spout as a two-handle wall-mounted mixer DN 15, fitting group I, for wall mounting for baths in the healthcare and nursing sector, for connecting to hot and cold water. Ceramic valve cartridge with rotary handle for flow regulation, mixer water shut-off, as well as integrated diverter for bathtub and hand shower. Thermostat-controlled mixer cartridge with expansion element and active scald protection, fail-safe against backflow as well as adjustable, turn-proof temperature stop, preset to 38 °C and option to carry out manual thermal


disinfection. Tap optimised for cleaning with ergonomically designed handles, scald-protected safe-touch housing with hand shower connection 13 l/min, G 1/2 B, bath spout with laminar jet controller 20 l/min and backflow preventer. All-metal construction, high-polished chrome-plated. Double-walled tap housing for reducing the heat transfer from the tap housing to the cold water line, with volume-reduced and smooth water lines. With adjustable connections with strainers, fully covered by depth-adjustable screw rosettes. 180 mm bath spout projection.

Technical Data

circulation
compatible A3000 open
connection with pay water disp
adjustable flow time
functional principle
for hand shower
hygiene flushing
diameter nominal
inlet size
Locking mechanism
type of mixing
shower pipe draining
with shower set
surface finish casing
tailor made
temperature limit
thermal disinfection
type of mounting
type of operation
type of shower
water connection
position of water connection
with soap dish

no
no
not possible
no
manual
yes
no
DN 15
DN 15
Top section, ceramic
with thermostat
no
no
chromed
no
yes
manual thermal disinfection
wall mounting
manual operation
wall fitting
S-unions
from backside
no


Optional Accessories



Shower bracket

2030051217  
ACXX2008

Spare Parts



Service key Neoperl © Caché ©, STD,  
24 mm, grey

635231  
Z.635.231